

Available online at www.sciencedirect.com

ScienceDirect

journal homepage: www.elsevier.com/locate/hydro

Assessment of the adequacy of different Mediterranean waste biomass types for fermentative hydrogen production and the particular advantage of carob (*Ceratonia siliqua* L.) pulp

Joana Ortigueira ^{a,b}, Carla Silva ^b, Patrícia Moura ^{a,*}^a INEG, Laboratório Nacional de Energia e Geologia, Unidade de Bioenergia, Estrada do Papa do Lumiar, 1649-038 Lisboa, Portugal^b Instituto Dom Luís, Faculdade de Ciências, Universidade de Lisboa, 1749-016 Lisboa, Portugal

ARTICLE INFO

Article history:
Received 10 November 2017
Received in revised form
23 February 2018
Accepted 5 March 2018
Available online xxx

Keywords:

Dark fermentation
Clostridium butyricum
Carob pulp
Brewery's spent grain
Corn cobs
Microalgal biomass

ABSTRACT

The conversion of agro-industrial byproducts, residues and microalgae, which are representative or adapted to the Mediterranean climate, to hydrogen (H_2) by *C. butyricum* was compared. Five biomass types were selected: brewery's spent grain (BSG), corn cobs (CC), carob pulp (CP), *Spirogyra* sp. (SP) and wheat straw (WS). The biomasses were delignified and/or saccharified, except for CP which was simply submitted to aqueous extraction, to obtain fermentable solutions with 16.2–168.4 g total sugars L^{-1} . In small-scale comparative assays, the H_2 production from SP, WS, CC, BSG and CP reached 37.3, 82.6, 126.5, 175.7 and 215.8 mL ($g\ biomass^{-1}$), respectively. The best fermentable substrate (CP) was tested in a pH-controlled batch fermentation. The H_2 production rate was 204 mL ($L\ h^{-1}$) and a cumulative value of 39 L $H_2\ L^{-1}$ was achieved, corresponding to a H_2 production yield of 70.0 mL ($g\ biomass^{-1}$) or 1.6 mol (mol of glucose equivalents) $^{-1}$. The experimental data were used to foresight a potential energy generation of 24 GWh per year in Portugal, from the use of CP as substrate for H_2 production.

© 2018 Hydrogen Energy Publications LLC. Published by Elsevier Ltd. All rights reserved.

Introduction

Global warming and issues of national security due to dependence on oil and gas imports have increased the renewable energy research at an unprecedented rate during the last decade [64]. Regarding biomass use for biofuels, efforts based on the rational use of waste, crop leftovers and

agro-industrial byproducts must be undertaken, to avoid any competition between food and energy production [17]. Any analysis concerning the production and conversion of biofuels must take into consideration which renewable resources are available at a local and regional level, therefore depending on geographic location, climate specifications and biomass availability [55], while ensuring their possible exploration preserves the natural biodiversity, and soil, fodder and water

* Corresponding author.

E-mail addresses: joana.ortigueira@lneg.pt (J. Ortigueira), camsilva@fc.ul.pt (C. Silva), patricia.moura@lneg.pt (P. Moura).<https://doi.org/10.1016/j.ijhydene.2018.03.024>

0360-3199/© 2018 Hydrogen Energy Publications LLC. Published by Elsevier Ltd. All rights reserved.

Please cite this article in press as: Ortigueira J, et al., Assessment of the adequacy of different Mediterranean waste biomass types for fermentative hydrogen production and the particular advantage of carob (*Ceratonia siliqua* L.) pulp, International Journal of Hydrogen Energy (2018), <https://doi.org/10.1016/j.ijhydene.2018.03.024>

Acknowledgments

This manuscript is a result of the project POSEUR-01-1001-FC-000001 supported by POSEUR under the PORTUGAL 2020

Partnership Agreement, through the Cohesion Fund. Joana Ortigueira acknowledges FCT for the PhD grant SFRH/BD/107780/2015. The authors also thank the technical assistance of Céu Penedo (biomass characterisation) and Luís Ramalho (GC analysis).